



4700

IN-LINE SLIDER / LIFT & SLIDE

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 1.0$ (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: 1.42"

Maximum acoustic insulation: $R_w = 40$ dB

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 3* / 4**

Water tightness (EN 12208):

Class 7A

Wind resistance (EN 12210):

Class C5* / C2**

* Reference in-line slider test 70.87" × 86.61" / 2 sashes

** Reference lift & slide test 157.48" × 98.43" / 2 sashes

Security Test:



Passed

Reference test 94.49" × 94.49" / 2 sashes

SECTIONS	Frame 4.72" and 4.53" Three-rail 7.28" Sash 1.97"
PROFILE THICKNESS	Balcony 0.059"
MAXIMUM DIMENSIONS	Width (L) = 98.43" Height (H) = 118.11"
MAXIMUM WEIGHT/SASH	Slide 280 Kg Lift & Slide 300 Kg

Please consult maximum dimensions according to types.

EXTRUSION ALLOY

6063 T-5

POLYAMIDE STRIP LENGTH

Polyamide 6.6 reinforced with 25% fiberglass :
0.79" y 0.98"

OPENING POSSIBILITIES

Sliding of 2, 3, 4, 6 & 8 sashes 1 rail (1 sash + 1 fixed light) 2, 3 & 4 rails Galandage 1, 2, 3 & 4 sashes

FINISHES

Colour powder coating (RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

