

BWC-78

Thermal efficiency	
Uw*	0,89 W/m2K
U factor*	0.16* Btu/h·ft ² ·F
*	Glass: 4/14/4/14/4; gas: argon, warm edge spacer; window size: 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name	BWC 78
Installation depth	3.07 in
Number of chambers	n/a
Thermal Break	n/a
Number of seals	3
Glass	
Glazing package	4/14/4/14/4
Ug value	0,6 W/m2K
Glazing package thickness	1.575 in
Sound insulation of available glazing	---
Fittings	
Types	---
Hinges	surface
Anti-theft protection	1 Anti-theft catch for Tilt and Turn RU
Microventilation	Yes
Other	handle rotation lock with a lifter
Handles	
Colors	---
Handle model	1006
Dimensions	
Maximum window width – single sash	59 in
Maximum window height – single sash	99.4 in
Maximum window width - double sash with a movable post	81.9 in
Maximum window height – double sash with a movable post	99.4 in
Maximum sash area	3 m2
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg)	137.8 x 114.1 in lub 137.8 x 114.1 in