



# COR 70 OC HALF - HIDDEN SASH

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 1.0$  (W/m<sup>2</sup>K)

Please consult typology, dimensions and glazing.

## ACOUSTIC INSULATION

Maximum glazing: 2.17"

Maximum acoustic insulation:  $R_w = 44$  dB

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class E1800

Wind resistance (EN 12210):

Class C5

Reference test 48.43" x 58.27" / 2 Sashes

<b>SECTIONS</b>	Frame 2.76" - 9.13" Sash 3.07"	<b>EXTRUSION ALLOY</b>	6063 T-5
<b>PROFILE THICKNESS</b>	Window 0.059"	<b>POLYAMIDE STRIP LENGTH</b>	Polyamide 6.6 reinforced with 25% fiberglass: 1.38"
<b>MAXIMUM DIMENSIONS MAXIMUM</b>	Width (L) = 39.37" Height (H) = 66.93"	<b>GASKETS</b>	EPDM triple gasket
<b>WEIGHT/SASH</b>	160 Kg	<b>FOAMS</b>	Perimeter polyolefin foam in glazing rebate zone
<b>FINISHES</b>	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured	<b>OPENING POSIBILITIES</b>	<b>INWARD</b> Casement 1 & 2 sashes, tilt & turn 1 & 2 sashes, tilt.
<b>HARDWARE</b>	Optionally concealed hinges Optionally security hardware		

Please consult maximum dimensions according to types.

