



# COR GALICIA PREMIUM

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

Uw from 1.1 (W/mK)<sup>2</sup>

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: Sash: 1.57" Fijo: 1.18"

Maximum acoustic insulation: Rw = 40 dB.

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class E1050

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 48.43" × 58.27" 2 sashes.

SECTIONS	Frame 2.61" Sash 3.36"
PROFILE THICKNESS	Window 0.059" Door 0.063"
MAXIMUM DIMENSIONS	Width (L) = 55.12" Height (H) = 94.49"
MAXIMUM WEIGHT/SASH	100 Kg.

Please consult maximum dimensions according to types.

FINISHES	Colour powder coating (RAL, mottled, rough...) According Qualicoat > 60 microns
	Wood effect powder coating According to Qualideco standard
	Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25
	<b>TIMBER ALWAYS INWARDS</b> American oak, sapelly, mellis pine. More options upon request (use of ecological varnish without solvents, transparent and satin).

EXTRUSION ALLOY	
6063 T-5	
POLYAMIDE STRIP LENGTH	
Polyamide 6.6 reinforced with 25% fiberglass : Frame 0.58" Sash 0.63"	
GASKETS	
EPDM triple gasket	
OPENING POSIBILITIES	
INWARDS	Side hung, turn&tilt, tilt and parallel-tilt

